



Earthstone Matting combines nature-inspired design with high-performance entrance protection. Its irregular, tactile surface takes inspiration from naturally weathered stone, creating a calm, understated finish that complements timber, concrete, stone and other architectural materials.

Designed for premium commercial interiors, Earthstone delivers effective moisture absorption and dirt concealment while maintaining a refined, design-led appearance. Manufactured using regenerated ECONYL® nylon yarn and HydroTX™ moisture management technology, it balances aesthetics, durability and performance.



SYSTEM APPLICATIONS

Suitable for interior entrances.

Highly Recommended for:

- Luxury Hotels & Resorts
- Day Spas & Wellness Centres
- Health Retreats
- Medical & Allied Health Facilities
- Boutique Commercial Offices
- High-End Residential Developments
- Education Facilities
- Public Buildings
- Contemporary Commercial Entrances

EARTHSTONE MATTING

Inspired by Nature
Designed for Beautiful Spaces



TECHNICAL SPECIFICATION

GENERAL

- 5-year warranty (excluding wear & tear)
- Indoor commercial entrance matting
- High-traffic performance
- Regenerated ECONYL® nylon yarn
- Textured loop-pile construction
- HydroTX™ moisture management technology
- Exceptional dirt concealment
- Four nature-inspired colourways
- Colouring: piece-dyed
- Recessed or surface-mounted installation
- Australian fire and slip tested

PERFORMANCE


- Moisture absorption capacity (TNO W6034): approx. 5.6 L/m²
- Sand absorption: Class 3 — ≥90%
- Slip resistant to Australian Standards
- Fire tested to Australian Standards

ROLL SIZE


- 2.00 m × approx. 20 lm

All rolls are supplied with a 15 mm PVC edge. Supplied roll length may vary by up to ±15%


Colour Options




DEEP TIDE



SEA MIST



SALT AIR



COASTAL DUNE



LEARN
MORE



REQUEST
A QUOTE



REQUEST
A SAMPLE



SUSTAINABLE CHOICE

Earthstone is manufactured using regenerated ECONYL® nylon yarn, produced from recovered nylon waste including discarded fishing nets and other post-consumer materials.

By giving new life to existing resources, Earthstone supports more responsible material selection while maintaining the durability and performance required in commercial entrance environments.

HYDROTX™ TECHNOLOGY

HydroTX™ begins capturing moisture from the first few steps, absorbing up to three times more moisture during initial foot contact than conventional entrance matting.



SYSTEM INSTALLATION

For recessed matting, Birrus installation services are available.

Ensure the substrate is clean, dry, smooth and level before installation. Allow Earthstone to acclimatise to site conditions prior to cutting or fixing.

Installation methods and adhesives should be selected to suit the substrate and application. Contact Birrus for project-specific installation recommendations.

We recommend that the mat be unrolled and allowed to adjust to the climate for 8-24 hours.



CARE & MAINTENANCE

Daily maintenance

Vacuum regularly using a commercial vacuum cleaner with effective brush action to remove dry soil and debris.

Increase cleaning frequency in high-traffic areas and during wet weather. Attend to spills promptly and avoid over-wetting the product.

Periodic professional cleaning may be required depending on traffic levels and soiling.